posirot®
Magnetic Angle Sensors

PRDS27

Angle sensor for standard industrial applications



- **Measurement range 0°... 360°**
- **Protection class IP67**
- **Overall height 10 mm**
- **Contactless with external position magnet, wear-free**
-

Product versions

Digital output CANopen/SAE J1939 (optional redundant)



PRDS27 - Magnetic Angle Sensor

Version with Digital output CANopen/SAE J1939 (optional redundant)

Specifications

			Order options
Measurement range	0 ... 360°		
Output	CANopen CAN SAE J1939 CANopen, redundant CAN SAE J1939, redundant	1	**CANOP** **CANJ1939** **CANOPR** **CANJ1939R**
Resolution	0.05° max.		
Linearity	±1% (typical)		
Rated distance sensor / magnet	Depending on the position magnet		
Housing material	Plastic		
Mounting	Screws M4: DIN 912, DIN 6912, DIN 7984		
Protection class	IP67		
Connection	Cable 0.3 m with connector M12, 5 pin Deutsch connector, not shielded	2	**KAB0,3M-M12/CAN**
Shock	DIN EN 60068-2-27:2010, 100 g/11 ms, 100 shocks		
Vibration	DIN EN 60068-2-6:2008, 20 g 10 Hz-2 kHz, 10 cycles		
Temperature range	-40 ... +85°C		
Weight	20 g approx. (without cable)		
EMC	DIN EN 61326-1:2013		

Order code

PRDS27 – 1 – 2


Order example: PRDS27 – CANOP – KAB0,3M-M12/CAN

Accessories:

Position magnets(see from page 4)

Magnetic shield(see page 16)

Dimensions




A – Position magnet
B – Measuring area
C – Marking
D – Cable

Dimensions in mm [inch].
Dimensions informative only.
For guaranteed dimensions consult factory.

Position magnets

PRMAG20




A – Sensor
B – Marking

Order code	Weight	Material	Moment of inertia
PRMAG20	approx. 12 g	zinc coated steel, plastic	1.3 kgmm^2

A misalignment of the position magnet has an effect on the linearity.

Dimensions in mm [inch].
Dimensions informative only.
For guaranteed dimensions please consult factory.

PRMAG21




A – Sensor
B – Marking

Order code	Weight	Material	Moment of inertia
PRMAG21	approx. 3 g	zinc coated steel; plastic	0.1 kgmm^2

A misalignment of the position magnet has an effect on the linearity.

Dimensions in mm [inch]
Dimensions informative only.
For guaranteed dimensions please consult factory.

PRMAG22




A – Sensor
B – Marking


Order code	Weight	Material	Moment of inertia
PRMAG22	approx. 19 g	zinc coated steel, plastic	3 kgmm^2

A misalignment of the position magnet has an effect on the linearity.

Dimensions in mm [inch].
Dimensions informative only
For guaranteed dimensions please consult factory.

PRMAG-M10






A – Sensor
B – Marking
C – Thread M10

Order code	Weight	Material	Moment of inertia
PRMAG-M10	approx. 30 g	stainless steel A2	1.3 kgmm2

A misalignment of the position magnet has an effect on the linearity.

Dimensions in mm [inch].
Dimensions informative only.
For guaranteed dimensions please consult factory.

Measuring error by misalignment of the position magnet



Air gap (a)
Parallelism (b)
Lateral offset (c)

Sensor	Position magnet	Air gap [mm]	Parallelism [°]	Error by lateral offset [°]					
				0.2 mm	0.5 mm	1 mm	2 mm	3 mm	4 mm
PRAS27 PRDS27	PRMAG20	0 ... 7.5	0 ... 5	0.1	0.3	0.7	2	4.6	–
	PRMAG21	0 ... 2.5	0 ... 5	0.15	0.3	0.9	3.6	9.6	–
	PRMAG22	0 ... 10.5	0 ... 5	0	0	0.7	1.5	3.8	7
	PRMAG-M10	0 ... 3.5	0 ... 5	0.1	0.1	0.5	2	7	–


Output specification

Digital output CANopen

CANOP CANopen	CAN Specification	ISO 11898, Basic and Full CAN 2.0 B
	Communication profile	CANopen CiA 301 V 4.02, Slave
	Device profile	Encoder CiA 406 V 3.2
	Configuration services	Layer Setting Service (LSS), CiA Draft Standard 305 (transmission rate, node id)
	Error Control	Node Guarding, Heartbeat, Emergency Message
	Node ID	Default: 127; programmable via LSS or SDO
	PDO	3 TxPDO, 0 RxPDO, static mapping
	PDO Modes	Event-/Time triggered, Remote-request, Sync cyclic/acyclic
	SDO	1 server, 0 Client
	CAM	8 cams
	Certified	Yes
	Transmission rates	50 kBaud to 1 MBaud, default: 125 kBaud; programmable via LSS or SDO
	Bus connection	M12 connector, 5 pin
	Integrated bus terminating resistor	Adjustable by the customer
	Bus, galvanic isolated	No

Specifications	Excitation voltage	8 ... 36 V DC
	Excitation current	20 mA typical at 24 V DC 40 mA typical at 12 V DC, 80 mA max.
	Resolution	0.05° max.
	Stability (temperature)	±50 x 10^{-6}/°C f.s. (typical)
	Repeatability	1 LSB
	Operating temperature	See specification of the respective sensor
	Protection	Reverse polarity, short circuit
	Dielectric strength	1 kV (V AC, 50 Hz, 1 min.)
	EMC	DIN EN 61326-1:2013

Signal wiring
Connector M12, 5 pin




View to the sensor connector

Output signals	Connector pin no.	Cable color
Shield	1	brown
Excitation +	2	white
GND	3	blue
CAN-H	4	black
CAN-L	5	grey

CANOPR CANopen	CAN Specification	ISO 11898, Basic and Full CAN 2.0 B
	Communication profile	CANopen CiA 301 V 4.02, Slave
	Device profile	Encoder CiA 406 V 3.2
	Configuration services	Layer Setting Service (LSS), CiA Draft Standard 305 (transmission rate, node id)
	Error Control	Node Guarding, Heartbeat, Emergency Message
	Node ID	Default: 127 and 126; programmable via LSS or SDO
	PDO	3 TxPDO, 0 RxPDO, static mapping
	PDO Modes	Event-/Time triggered, Remote-request, Sync cyclic/acyclic
	SDO	1 server, 0 Client
	CAM	8 cams
	Certified	Yes
	Transmission rates	50 kBaud to 1 MBaud, default: 125 kBaud; programmable via LSS or SDO
	Bus connection	M12 connector, 5 pin
	Integrated bus terminating resistor	adjustable by the customer
	Bus, galvanic isolated	No

Specifications	Excitation voltage	8 ... 36 V DC
	Excitation current	40 mA typical at 24 V DC 80 mA typical at 12 V DC, 120 mA max.
	Measuring rate	1 kHz (asynchronous)
	Stability (temperature)	±50 x 10^{-6}/°C f.s. (typical)
	Repeatability	1 LSB
	Operating temperature	See specification of the respective sensor
	Protection	Reverse polarity, short circuit
	Dielectric strength	1 kV (V AC, 50 Hz, 1 min.)
	EMC	DIN EN 61326-1:2013

Signal wiring
Connector M12, 5 pin



View to the sensor connector

Output signals	Connector pin no.	Cable color
Shield	1	brown
Excitation +	2	white
GND	3	blue
CAN-H	4	black
CAN-L	5	grey

Digital output CAN SAE J1939


CANJ1939 SAE J1939 CAN	CAN Specification	ISO 11898, Basic and Full CAN 2.0 B	
	Transceiver	24V-compliant, not isolated	
	Communication profile	SAE J1939	
	Baud Rate	250 kbit/s	
	Internal termination resistor	adjustable by the customer	
	Address	Default 247d, configurable	

NAME Fields	Arbitrary address capable	1	Yes
	Industry group	0	Global
	Vehicle system	7Fh (127d)	Non specific
	Vehicle system instance	0	
	Function	FFh (255d)	Non specific
	Function instance	0	
	ECU instance	0	
	Manufacturer	145h (325d)	Manufacturer ID
	Identity number	0nnn	Serial number 21 bit

Parameter Group Numbers (PGN)	Configuration data	PGN EF00h	Proprietary-A (PDU1 peer-to-peer)
	Process data	PGN FFnnh	Proprietary-B (PDU2 broadcast); nn Group Extension (PS) configurable

Specifications	Excitation voltage	8 ... 36 V DC
	Excitation current	20 mA typical at 24 V DC 40 mA typical at 12 V DC 80 mA max.
	Measuring rate	1 kHz (asynchronous)
	Stability (temperature)	±50 x 10^{-6}/°C f.s. (typical)
	Repeatability	1 LSB
	Operating temperature	See specification of the respective sensor
	Protection	Reverse polarity, short circuit
	Dielectric strength	1 kV (V AC, 50 Hz, 1 min.)
	EMV	DIN EN 61326-1:2013

Signal wiring Connector M12, 5 pin	**Output signals**	**Connector pin no.**	**Cable color**
	Shield	1	brown
	Excitation +	2	white
	GND	3	blue
	CAN-H	4	black

 View to the sensor connector	CAN-L	5	grey


CANJ1939R CAN SAE J1939	CAN Specification	ISO 11898, Basic and Full CAN 2.0 B	
	Transceiver	24V-compliant, not isolated	
	Communication profile	SAE J1939	
	Baud Rate	250 kbit/s	
	Internal termination resistor	Adjustable by the customer	
	Address	Default 247d and 246d, configurable	

NAME Fields	Arbitrary address capable	1	Yes
	Industry group	0	Global
	Vehicle system	7Fh (127d)	Non specific
	Vehicle system instance	0	
	Function	FFh (255d)	Non specific
	Function instance	0	
	ECU instance	0	
	Manufacturer	145h (325d)	Manufacturer ID
	Identity number	0nnn	Serial number 21 bit

Parameter Group Numbers (PGN)	Configuration data	PGN EF00h	Proprietary-A (PDU1 peer-to-peer)
	Process data	PGN FFnnh	Proprietary-B (PDU2 broadcast); nn Group Extension (PS) configurable

Specifications	Excitation voltage	8 ... 36 V DC
	Excitation current	40 mA typical at 24 V DC 80 mA typical at 12 V DC 120 mA max.
	Measuring rate	1 kHz (asynchronous)
	Stability (temperature)	±50 x 10^{-6}/°C f.s. (typical)
	Repeatability	1 LSB
	Operating temperature	See specification of the respective sensor
	Protection	Reverse polarity, short circuit
	Dielectric strength	1 kV (V AC, 50 Hz, 1 min.)
	EMV	DIN EN 61326-1:2013

Signal wiring Connector M12, 5 pin	**Output signals**	**Connector pin no.**	**Cable color**
	Shield	1	brown
	Excitation +	2	white
	GND	3	blue
	CAN-H	4	black
	CAN-L	5	grey



View to the sensor connector

Accessories
PRAS27 Magnetic Shield

An optional shield plate is available for the angle sensors PRAS27 and PRDS27. It can reduce the effect of residual magnetizing in case the sensor has to be mounted on a ferromagnetic material.

Order code magnetic shield:

PRAS27-MSHIELD

